

MAP2


MODULAR ACCESS PANEL

Cutting edge simplicity®



ACCESS CONTROL AS A SERVICE

- 100,000 users -1024 readers
- Subscription based
- No software to install
- Managed via browser from anywhere
- Free iOS and Android app



CLIENT-SERVER SOFTWARE

- 100,000 users -1024 readers
- Windows based
- Up to 10 First Access clients
- Automatic panel discovery

One panel, *two solutions*

The MAP2 Modular Access Panel is totally self-contained and puts support for up to 8 doors and 100,000 users. It utilizes a powerful quad core processor, is network ready and contains status LEDs making it simple to commission and maintain. The MAP2 is factory provisioned for 2, 4, 6, or 8 doors and can be field upgraded up to a maximum of 8 doors by simply purchasing a new provisioning code. When you are ready to upgrade, all you will have to add is readers and locks. You only pay for what you need!

There are many benefits to using the same MAP2 building block for CloudACS™ and First Access®. One of the biggest is that users can easily move between solutions as their needs change. If you start with a First Access® system, you can easily migrate to CloudACS™. If you no longer require a CloudACS™ solution, you can easily change back to First Access®. No other access control manufacturer can offer this kind of future proofing.




MAP2

MODULAR ACCESS PANEL

FEATURES

FEATURES*	MAP2 (MODULAR ACCESS PANEL)
Doors	2, 4, 6, or 8
Onboard Network TCP/IP	Yes
Self-contained	Yes
Audit Buffer (transactions)	10,000
Facility Codes (FC)	Unlimited
Card Capacity	100,000 with any FC or ID
Multiple Credentials Per User	Yes - 5
Binary Wiegand Support	ANY format up to 64 bits
37-bit Cansec Support	Yes
26-bit Support	Yes
Corporate 1000 - 35/48-bit	Yes
Onboard Auto Void/Validate	Yes
Schedule Time Resolution	1 min
Access Schedules	256
Unlock Schedules	4
Output Schedules	8
Shunt Schedules	8
Manual Shunt	Yes
Scheduled Commands	Yes
Low 12V DC Power Warning	Yes

TYPICAL CONFIGURATION



*NOTE: Not all features and capacities are supported on all solutions.

SPECIFICATIONS

Size	7" (L) x 7" (W) [18 cm (L) x 18 cm (W)]
Weight	300 g [10.7 oz]
Operating Temperature	-20°C to 60°C [-4°F to 140°F]
Power Requirement	12 VDC / 1.5 A [Max. Current (including 8 proximity readers with 100 mA each)]
Warranty	5 years



PART NUMBERS

DOOR CONTROL:

- CA-MAP22H_ (MAP2 2-Door Configuration)
- CA-MAP24H_ (MAP2 4-Door Configuration)
- CA-MAP26HF (MAP2 6-Door Configuration)
- CA-MAP28HF (MAP2 8-Door Configuration)
- CA-MAP20HF (MAP2 16-Input/16-Output Configuration)

- CA-MAP22U4H_ (MAP2 2-Door Provisioning Upgrade to 4-Door Configuration)
- CA-MAP24U6HF (MAP2 4-Door Provisioning Upgrade to 6-Door Configuration)
- CA-MAP26U8HF (MAP2 6-Door Provisioning Upgrade to 8-Door Configuration)

ELEVATOR CONTROL:

- CA-MAP2E16 (MAP2 Elevator Controller - 16 floor)
- CA-MAP2E32 (MAP2 Elevator Controller - 32 floor)
- CA-MAP2E48 (MAP2 Elevator Controller - 48 floor)
- CA-MAP2E64 (MAP2 Elevator Controller - 64 floor)

"_" replaced with:

- F - First Access
- C - CloudACS



Cansec Systems Ltd. | 3105 Unity Drive | Unit 9 | Mississauga | Ontario | L5L 4L2 | Canada

T (905) 820-2404 F (905) 820-0301 TF 1.877.545.7755

cansec.com